

KORAL-KSE

THE ORIGINAL FACELIFTED



CLASSIC LINE

3 YEARS OF WARRANTY

NEW BODY

Available during 2023 season depending on the stock of the old body available

- ➔ 500 grams lighter compared with the original
- ➔ Optimised and super-silent hydraulic system
- ➔ Visibility of the internal prefilter, easy access
- ➔ Impeller in corrosion-resistant and hard-wearing Noryl®
- ➔ Double drain, easy opening (no tools required)
- ➔ Usage: for residential pools up to 177 m³
- ➔ Prefilter size: 3.5 L

	Code	Ref.	Hp	P2 (W)	P1 (W)	Amps (A)	A (mm)	Flow rate (m ³ /h)*	Weight (kg)	Pack. (mm)	qty/pallet	
SINGLE PHASE	010401221010	KSE 33 M	0.33	243	450	2.5	503	4.8	10.7	330 x 255 x 650	30	
	010411320110	KSE 50 M	0.50	368	580	3.2	550	7.5	12	330 x 255 x 650	30	
	010411420110	KSE 75 M	0.75	552	750	3.8	550	11.5	13	330 x 255 x 650	30	
	010411520110	KSE 100 M	1.00	736	1000	5.0	550	15.4	13.5	330 x 255 x 650	30	
	010421120120	KSE 150 M	1.50	1104	1600	7.5	580	21.9	16	330 x 255 x 650	25	
	010421220120	KSE 200 M	2.00	1472	1920	9.0	580	25.7	17	330 x 255 x 650	25	
	010421420120	KSE 300 M	3.00	2208	2600	12.5	620	29.5	22	330 x 255 x 650	25	
THREE PHASE	010411350110	KSE 50 T1	0.50	368	580	2.45/1.4	550	7.5	11.5	330 x 255 x 650	30	IE2 ✓
	010411450110	KSE 75 T1	0.75	552	750	3/1.7	550	11.5	12.5	330 x 255 x 650	30	IE2 ✓
	010471050110	KSE 100 T1 IE3	1.00	736	1000	3.4/2	550	15.4	13	330 x 255 x 650	25	IE3 ✓
	010471150110	KSE 150 T1 IE3	1.50	1104	1600	5/2.9	580	21.9	15.5	330 x 255 x 650	25	IE3 ✓
	010481250110	KSE 200 T1 IE3	2.00	1472	1920	6.1/3.5	580	25.7	16.5	330 x 255 x 650	25	IE3 ✓
	010481350110	KSE 300 T1 IE3	3.00	2208	2060	8.3/5	620	29.5	21.5	330 x 255 x 650	25	IE3 ✓

P1 Input power - P2 Output power

* 10 m water column pressure

M.O.Q. :1

60 Hz on request, ask for conditions

Technical Specifications

Max. water temp. / Max. pressure	50°C / 2,5 bar
Connection (DIN slip included, for others please ask)	Ø 50 (0,33-1 hp) Ø 63 (1,5-3,00 hp) All bodies have 2" thread. Possibility to have ANSI connection
Mechanical seal	AISI 316, suitable for salt water
Motor specifications	Class F, IP55, 50 Hz 2.850 rpm
Housing/impeller/strainer/lid	PP + F.G/Noryl®/PP/SAN®

